

TOUCH-UP (Belt) Conveyor Line

1. Dimension: 400 (W) * 750 (H) * 3000(L) mm (3M as a unit)
2. Power set: US 60W * 220V * single phase, V=1.4M/ minute (adjustable speed)
3. Carriage belt: W400 * 2T* U-10, imported green anti-static belt
4. Carriage trail: 2T*W400* full trail. (3M)
5. Carriage wheel: ϕ dia.57 X L420* route
6. Body structure: the Aluminum pushes, 40*60
7. Foot stand structure: the Aluminum pushes, 40*60
8. Working board: 18T*300W, anti-static board with anti-static buttons and clips.
9. Lamp structure: the Aluminum pushes, 40*40*2000/P*H1900
10. Fluorescent lamps: 220V*40W* single tube, 2 sets in a unit.
11. Plug: 220V * 4 socket * 1500/P with ground line (universal), located in both sides
12. Air pressure vassal: SGP 3/4* 1/2 quick adapter * 1000 /P, beneath the central food stand, double outlets
13. Hangers for screw driver/ instrument: the Aluminum pushes, 23*25 with pulley 1000 / P
14. Shelf: Plywood board with common PVC Surface, 12T*W400
15. Instruction Holder: Acrylic, Green 2.5T*H320*W450*1000/P * 1 piece in the middle line
Acrylic, Transparent 1.5T*H320*W450*1000/P* 2 pieces
16. Electrical devices: Control Box, 1 set with speed regulator
17. The belt conveyer in the middle for carriage only.
18. Power and air pressure should be arranged by end users themselves.

Lead time: 20-25 days after P.O. confirmation

INCO Term: FOB Taiwan

Payment: T/T in advance.

Shipment: to be advised by buyer

Package: wooden case with fumigation.

(With Shelf)



(Without Shelf)

