



**Round Soldering Pot  
SP-060, SP-080, SP-100**

## FEATURES

- The pot is designed for easy movement and installment right after plug in.
- The automatic I.C.I. temperature control ensures great safety.
- Besides, special designs prevent from oxide.
- Application: Melting wax, welding electronic parts, tin boiler, wires, desoldering parts for through hole PCB, connector and etc.

## SPECIFICATIONS

- H = I.C. Thermal Control
- PV = Temperature Display

代號 Model	H=IC control有溫控 PV=Display 數位顯示	內徑規格 Spec.	尺寸 DxH Size (cm)	熔錫量 Volume (kg)	重量 Weight(kgs)	瓦特數 Wattage (W)	溫度 Temperature	電壓 Voltage
SP-60H / PV		6 cm	6x4	1.2	2.2	350	0~500 °C	110V or 220V
SP-80H / PV		8 cm	8x4	2	3.1	450	0~500 °C	
SP-100H / PV		10 cm	10x4	2.5	4.7	550	0~500 °C	



**Round Soldering Pot  
SP-060, SP-080, SP-100**

#### 產品說明

- 本錫爐為輕便型、溫度自動控制、無段、可變調整、安全性高、錫渣撥放設計
- 適用於：熔臘、焊錫、鍍電子零件、電線、小型 PC 板、拔 IC 零件。

#### 產品規格

代號 Model	H=IC control有溫控 PV= Display 數位顯示	內徑規格 Spec.	尺寸 DxH Size (cm)	熔錫量 Volume (kg)	重量 Weight(kgs)	瓦特數 Wattage (W)	溫度 Temperature	電壓 Voltage
SP-60H / PV		6 cm	6x4	1.2	2.2	350	0~500 °C	110V or 220V
SP-80H / PV		8 cm	8x4	2	3.1	450	0~500 °C	
SP-100H / PV		10 cm	10x4	2.5	4.7	550	0~500 °C	